

Standard Pliers

Standard Retaining Ring Pliers - Inch & Metric

Rotor Clip Standard Retaining Ring Pliers are made of high carbon, heat treated steel and produced to exacting QC specifications. They feature stop and return springs for problem-free installation/removal of retaining rings. This eliminates overspreading of external retaining rings, and speeds the assembly/removal of internal retaining rings by orienting plier to exact location of lug holes. Most Rotor Clip retaining ring pliers have exclusive air-cushioned handles.





Inch Plier Dimensions




INTERNAL STANDARD PLIERS







GENERAL DIMENSIONS (inches)



Internal Inch

For use with the following inch retaining rings:







	LUIMIDA		•					<u> </u>	HEIDIE DIN		1111011100	',	
											CLOSED	POSITION	
R	ing Series	/Size Rang	ge	ROTOR	45°	90°			Tip	Cleara	nce	Length	
HO-BH	IO-VHO	Н	01	CLIP	TIP	TIP	Weight	Tip	Length			Std.	
FROM				PLIERS	PLIERS	PLIERS	lbs.	Dia.	Α	В	C	Tip	Width
-25	-25 -31 -62 -		-	RPS-100	RPS-104	RPS-109	.15	.025	9/32	7/8	1-7/8	5-1/2	1-7/8
-37			-100	RP-100	RP-104	RP-109	.15	.038	9/32	7/8	1-7/8	5-1/2	1-7/8
-62	-102	-106	-137	RPL-100	RPL-104	RPL-109	.15	.047	9/32	7/8	1-7/8	5-1/2	1-7/8
-106	-175	-143	-200	RP-300	RP-304	RP-309	.17	.070	11/32	7/8	2-1/8	6-7/16	2-1/4
-181	-181 -300 -206 -300			RP-500	RP-504	RP-509	.62	.090	7/16	1-1/8	2-3/4	9	2-1/4

External Inch

For use with the following inch retaining rings:














	CVTCD	IAL OTA	NDADD	DLIEBO						OF.	NEDAL D	MENCIO	MC (inch					
١	EXIER	NAL STA	NDARD	PLIERS									GE	NERAL D				
g																POSITIO	N	
			Ring	g Series,	/Size Ra	nge			ROTOR	45°	90°			Tip	Clea	rance	Length	
Ī	SH-BS	H-VSH	S	HI	SI	ŀR	SI	HF	CLIP	TIP	TIP	Weight	Tip	Length			Std.	
	FROM	THRU	FROM	THRU	FROM	THRU	FROM	THRU	PLIERS	PLIERS	PLIERS	lbs.	Dia.	Α	В	C	Tip	Width
[-12	-	-	-	-	•	-		RP-12	RP-2124	RP-2129	.05	.023	7/32	1/2	1-1/8	5-5/16	1-1/2
	-15		•	-	-	ı	-	ı	RP-15	RP-2154	RP-2159	.05	.023	7/32	1/2	1-1/8	5-5/17	1-1/2
[-18	-23	-	-	-	í	-	í	RP-18	RP-2184	RP-2189	.05	.023	7/32	1/2	1-1/8	5-5/18	1-1/2
	-25	-66	-50	-78	-39	-47	-	ı	RP-200	RP-204	RP-209	.15	.038	9/32	1	2	5-1/2	2-1/2
. [-68	-87	-81	-100	-50	-66	-	-	RPL-200	RPL-204	RPL-209	.15	.047	9/32	1	2	5-1/2	2-1/2
	-93	-143	-106	-200	-	·	-	-	RP-400	RP-404	RP-409	.19	.070	11/32	1	2-3/8	7	2-7/8
	-150	-350	-215	-334	-	1	-	-	RP-600	RP-604	RP-609	.44	.115	7/16	1-1/4	3-1/16	9-1/8	4-1/4
	-	-	-	-	-75	-98	-31	-75	RPA-2	RPA-245	RPA-290	.22	.070	9/16	1	2	7-1/4	2-1/2

External pliers RP-12, RP-15 & RP-18 are available in the standard version with shielded tips. The 45° and 90° versions are unshielded. Both are equipped with fixed stops to prevent overspreading of the external retaining rings during installation or removal.

Metric Plier Dimensions







Please wear protective eyeware while installing and removing retaining rings & hose clamps.

Internal Metric For use with the following metric retaining rings:





METRIC INTERNA	L PLIERS (All Dime	nsions in mi	m)							Y COMPRESS Utting) cond	
Ring Series	/Size Range	ROTOR	45°	90°			Tip	Ti	ip	Overall	Max Width
DHO (DIN 472)	, DHT (DIN 984)	CLIP	TIP	TIP	Weight	Tip	Length	Clear	ance	Length	Across
FROM	FROM THRU		PLIERS	PLIERS	Kg	Dia.	A	В	C	Straight Tip	Handle
-8	-8 -9		RPI-045	RPI-090	0.07	0.9	8	19	48	140	45
-10	-17	RPI-1	RPI-145	RPI-190	0.07	1.3	8	19	48	140	45
-18	-30	RPI-2	RPI-245	RPI-290	0.1	1.8	10	25	55	165	60
-31	-83	RPI-3	RPI-345	RPI-390	0.23	2.3	14	30	70	230	65
-85	-100	RPI-4	RPI-445	RPI-490	0.42	3.2	20	45	70	300	55

External Metric For use with the following metric retaining rings:





METRIC EXTERNA	L PLIERS (All Dime	ensions in m	m)					FREE	(UNEXP	ANDED) COI	NDITION
										Overall	Max
Ring Series	s/Size Range	ROTOR	45°	90°			Tip	Ti	р	Length	Width
DSH (DIN 471)	, DST (DIN 983)	CLIP	TIP	TIP	Weight	Tip	Length	Clear	ance	Straight	Across
FROM	FROM THRU		PLIERS	PLIERS	Kg	Dia.	Α	В	C	Tip	Handle
-3	-9	RPA-0	RPA-045	RPA-090	0.07	0.9	8	22	38	140	75
-10	-17	RPA-1	RPA-145	RPA-190	0.07	1.3	8	22	38	140	75
-18	-30	RPA-2	RPA-245	RPA-290	0.1	1.8	14	25	50	185	100
-31 -82		RPA-3	RPA-345	RPA-390	0.23	2.3	14	30	75	230	105
-85 -100		RPA-4	RPA-445	RPA-490	0.46	3.2	20	45	80	300	175



Ratchet & Grip Ring Pliers






Ratchet Retaining Ring Pliers


Assemble large retaining rings up to 10" in diameter with ease and comfort using Rotor Clip Ratchet Pliers. Spring loaded mechanisms compress or expand large rings through gradual "steps." Plier locks at the desired size without continued pressure on the handles.


(Note: Ratchet Pliers do not include plier tips, which must be purchased separately.)











RATCHET	PLIERS	INTERN	IAL**							GE	NERAL D	IMENS	IONS (inc	hes)	
													CLOSED	POSITION	1
Ring	Series/	Size Rar	ige	PLIERS	STD.	45°	90°	TIP			Tip	Clea	arance	Length	
HO-BHC	OHV-C	Н	01	W/OUT	TIPS	TIPS	TIPS	COLOR	Weight	Tip	Length			Std.	
FROM	THRU	FROM	THRU	TIPS				CODE	lbs.	Dia.	Α	В	C	Tip	Width
-181	-237	-206	-250	RP-27R	RP-5021R	RP-5023R	RP-5024R	GOLD	.70	.093	15/32	1-3/8	3-13/32	10-5/8	3
-244	-300	-262	-300	RP-27R	RP-5005R	RP-5007R	RP-5008R	BLACK	.70	.108	15/32	1-3/8	3-13/32	10-5/8	3
-306	-400	-315	-400	RP-27R	RP-5009R	RP-5012R	RP-5013R	SILVER	.70	.120	15/32	1-3/8	3-13/32	10-5/8	3
-306	-600	-315	-400	RP-900	RP-7801R	RP-7845R	RP-7890R	BLACK	1.9	.120	1/2	1-3/4	3-1/2	16	3-7/8
-625	-1000	-	-	RP-1100	RP-71001R	RP-71451R	RP-71901R	BLACK	5.0	.150	1-5/32	1-3/4	4-5/16	28	6-1/2
**DI IFRS	: AND DI	IFR TIP	TZLIM 2	RE ORDER	ED TOGETHE	TO BE LISAR	RE TIPS ARE	INTERCHA	NIGEARL F	FOR I	NTERNAL	VVID E	YTERMAL	IISE	

^{**}PLIERS AND PLIER TIPS MUST BE ORDERED TOGETHER TO BE USABLE. TIPS ARE INTERCHANGEABLE FOR INTERNAL AND EXTERNAL USI

Internal For use with following ret	the
HO	HOI





RATCH	ET PLIE	RS EXT	ERNAL	**								GE	NERAL D	IMENS	ONS (ii	nches)	
	Ring	Series/	Size Ra	ange		PLIERS	STD.	45°	90°	TIP			Tip		CLOSÈI rance	POSITION Length	
SH-BSH-VSH FROM THRU FRO			HI		łR	W/OUT	TIPS	TIPS	TIPS	COLOR	Weight		Length	Oicai	unoc	Std.	
FROM	THRU	FROM	THRU	FROM	THRU	TIPS				CODE	lbs.	Dia.	A	В	C	Tip	Width
-	-	-	-	-106	-137	RP-28R	RP-5021R	RP-5023R	RP-5024R	GOLD	.70	.093	15/32	1-3/8	3-3/8	10-5/8	4-11/32
-150	-375	-215	-325	-	-	RP-28R	RP-5009R	RP-5012R	RP-5013R	SILVER	.70	.120	15/32	1-3/8	3-3/8	10-5/8	4-11/32
-	-	-	-	-150	-175	RP-1000	RP-8002R	RP-8452R	RP-8902R	BLACK	1.9	.108	5/8	2-1/2	3-5/8	14-1/2	13
-354	-650	-350	-393	-193	-200	RP-1000	RP-7801R	RP-7845R	RP-7890R	BLACK	1.9	.120	5/8	2-1/2	3-5/8	14-1/2	13
675	050					DD 1200	DD 69001D	DD 60/61D	DD 60001D	DIVUK	2.2	170	1 5/22	2 1/2	1 7/9	10 1//	1/

^{-675 | -950 | - | - | - |} RP-1200 | RP-68001R | RP-68451R | RP-68901R | BLACK | 2.2 | 1.170 | 1-5/32 | 2-1/2 | 4-7/8 | 18-1/4 | **PLIERS AND PLIER TIPS MUST BE ORDERED TOGETHER TO BE USABLE. TIPS ARE INTERCHANGEABLE FOR INTERNAL AND EXTERNAL USE.



For use with the following retaining rings:













Grip Ring Retaining Ring Pliers

Rotor Clip Grip Ring Pliers are designed for SHF & DSF external (shaft) friction rings. The pliers are made of forged Chrome Vanadium steel with non-slip solid tips, and the handles have a non-slip plastic coating.

Please wear protective eyeware while installing and removing retaining rings & hose clamps.

HEAVY DUTY PLI											
	Ring Serie	s/Size Range		ROTOR							
SI	SHF DSF										
(iı	1.)	(m	PLIERS								
FROM	THRU	FROM	THRU								
-6	-9	-1.5	-4	RPN-G0							
-12	-15	-4	-7	RPN-G1							
-18	-25	-5	-13	RPN-G2							
-31	-75	-14	-18	RPN-G3							

External
For use with the following retaining rings:







Convertible & Heavy-Duty Pliers


Convertible Retaining Ring Pliers


Convert quickly and easily from internal to external pliers and back again. This two-in-one capability is cost effective and ideal for handling a variety of applications with a minimum number of tools. Simply move the screw to the other hole and tighten with finger pressure to convert quickly to an internal/external plier.











Please wear protective eyeware while installing and removing retaining rings & hose clamps.

Internal For use with the following retaining rings:





0	00	0	
	1		
BHC)[0)
√ 0 €	✓ ¥	(a)	/ 1

CON	VERT	IBLE PLIE	RS, INTER	NAL RING	SERIES			GENERAL DIMENSIONS (inches)							
												CLOSED	POSITION		
	Ri	ng Series	/Size Ranç	je	ROTOR	45°	90°			Tip	Clear	ance	Length		
Н	O-BH	0-VH0	H	OI	CLIP	TIP	TIP	Weight	Tip	Length			Std.		
FR	FROM THRU FROM THRU			THRU	PLIERS	PLIERS	PLIERS	lbs.	Dia.	A	В	C	Tip	Width	
-3				-100	RP-120	RP-124	RP-129	.19	.038	9/32	1-3/16	1-5/8	5-5/8	1-3/4	
-4	45	-102	-106	-137	RP-320	RP-324	RP-329	.19	.047	9/32	1-3/16	1-5/8	5-5/8	1-3/4	
-1	06	-175	-143	-200	RP-340	RP-344	RP-349	.45	.070	11/32	1-7/16	1-7/8	7-7/8	3-5/16	
-1	81	-206	-206	-212	RP-560	RP-564	RP-569	.55	.090	5/8	1-3/4	3	9-1/4	4-1/2	

External For use with the following retaining rings:





)	(BSH)
	400
	II VICII II -

	CONVERT	IBLE PL	.IERS, EX	(TERNA	L RING S	SERIES						GENERAL DIMENSIONS (inches)						
			Rina	Series/	Size Rar	nne									C	LOSED	POSITIO	N
:			illing	OCI ICS/	DIZC ITAI	igu			ROTOR	45°	90°			Tip	Cleara	ince		
	SH-BSF	I-VSH	SI	H	SH	łR	SI	HF	CLIP	TIP	TIP	Weight	Tip	Length				
	FROM	THRU FROM THRU FROM THRU FR					FROM	THRU	PLIERS	PLIERS	PLIERS	lbs.	Dia.	Α	В	C	Length	Width
	-25	-60	-50	-78	-39	-47	-12	-25	RP-120	RP-124	RP-129	.19	.038	9/32	1-3/8	1-5/8	5-5/8	2-9/16
	-68	-87	-81	-100	-50	-66	-31	-37	RP-320	RP-324	RP-329	.19	.047	9/32	1-3/8	1-5/8	5-5/8	2-9/16'
l	-93	-143	-106	-200	-75	-98	-43	-75	RP-340	RP-344	RP-349	.45	.070	11/32	1-11/16	1-7/8	7-7/8	3-15/16
	-150	-200	-	-	-	-	-	-	RP-560	RP-564	RP-569	.55	.090	5/8	1-7/8	3	9-1/4	4-1/2

Heavy-Duty Retaining Ring Pliers

Rotor Clip Heavy-Duty Retaining Ring Pliers are designed to perform with excessive use - up to 10 times longer than standard retaining ring pliers. The pliers are made of forged Chrome Vanadium steel, and the handles have a non-slip plastic coating. They feature inserted tips of high density drawn spring wire and a precise, smooth operating screw joint. Large contact faces on the tips helps to eliminate distortion of the ring, and the slim head style allows for use in confined areas.



Internal

For use with the following retaining rings:





6		6
MI	10	

ш	HEAVY DUTY PLIERS - INTERNAL (Inch & Metric)												
	Ring Series/Size Range											90°	TIP
	HO		HOI		DHO (DIN 472)		DHT (DIN 984)		MHO		CLIP	CLIP	DIAMETER
									(ANSI Metric)		PLIERS	PLIERS	
	(in.)		(in.)		(mm)		(mm)		(mm)				
	FROM	THRU	FROM	THRU	FROM	THRU	FROM	THRU	FROM	THRU			(mm)
	-37	-56	-75	-100	-8	-13	-	-	-8	-15	RPN-J0	RPN-J01	0.9
	-62	-102	-106	-137	-12	-25	-16	-25	-15	-26	RPN-J1	RPN-J11	1.2
	-106	-175	-143	-200	-19	-60	-19	-60	-27	-60	RPN-J2	RPN-J21	1.8
	-181	-300	-206	-300	-40	-100	-40	-100	-62	-100	RPN-J3	RPN-J31	2.3

External For use with the

following retaining rings:







HEAVY DUTY PLIERS - EXTERNAL (Inch & Metric)												
Ring Series/Size Range										ROTOR	90°	TIP
S	SH		SHI		SHR		DSH (DIN 471)		MSH		CLIP	DIAMETER
						DST (DIN 983)		(ANSI Metric)		PLIERS	PLIERS	
(ir	1.)	(in.)		(in.)		(mm)		(mm)				
FROM	THRU	FROM	THRU	FROM	THRU	FROM	THRU	FROM	THRU			(mm)
-25	-66	-50	-78	-39	-47	-3	-10	-4	-12	RPN-A0	RPN-A01	0.9
-68	-87	-81	-100	-50	-66	-10	-25	-13	-23	RPN-A1	RPN-A11	1.2
-93	-143	-106	-220	-75	-98	-19	-60	-24	-36	RPN-A2	RPN-A21	1.8
-150	-350	-215	-350	-	•	-40	-100	-38	-90	RPN-A3	RPN-A31	2.3